


AV961G Series

HDMI Extender over 2 CAT5, 5E or 6 Cables



Features/Advantages	Description	Applications
<ul style="list-style-type: none"> Fully automatic equalized up to 40dB, no system controls are required Fully supports HDMI v1.3 and HDCP compliant devices 1080p/60Hz, 1080i, 720p, up to 165 ft. (50 m) 1080i/60Hz, 720p, up to 264 ft. (80 m) Supported PC resolutions up to 1920x1200/60Hz Rugged metal housing with 2 LED indicators for "Power" and "EQ on" Transmitter automatically converts HDMI signal to CAT5 TMDS signal Auto signal equalizer with auto feedback amplification adjustment Easy "Plug and Play" One year warranty 	<p>The ETS HDMI CAT5/6 Extender (AV961G) gives excellent HD signal transmission with surround sound along with a high resolution picture. The ETSAV961G has signal transmission distances up to 115 feet (35m) in 1080p HDMI format. Using two Cat5/6 cables, users can extend HDMI sources from sources compliant with TMDS connecting with distant display monitors including HDMI/DVI enabled TVs or LCD PC monitors.</p> <p>A permanent installation using Cat5 or 6 cables in the wall will pass building inspections. HDMI cables do not pass.</p> <p>The ETS HDMI CAT5/6 Extender includes (1) transmit, (1) receiver and 5V power supply.</p> <p>Notes: 1. HDMI cables are sold separately. Available in 3 ft, 6 ft, 10 ft and 15 ft. Sold only in sets. 2. Will not support mini Mac HDMI or mini display port.</p>	<ul style="list-style-type: none"> Auditoriums Churches Classrooms Digital Signage Home Theaters Information Kiosks Conference Rooms Monitoring Stations Schools Trade Shows

Specifications		Product Ordering Information	
Video bandwidth	2.25 Gbits/s per channel	AV961G	HDMI CAT5 Extender, (1) Transmit + (1) Receive and power supply (Only sold in sets.)
Support resolution	1080i 50/60Hz, 1080p 50/60Hz, 480i/480p, 576i/576p, 720p 50/60Hz	EC-HDMI-3	3.00 ft HDMI cable, male to male connector
Support audio	Dolby-AC3, DTS-HD, DTS7.1, LPCM, DSD	EC-HDMI-6	6.00 ft HDMI cable, male to male connector
DDC signal	5 volts peak-to-peak	EC-HDMI-10	10.00 ft HDMI cable, male to male connector
Clock adjustment phases	6	EC-HDMI-15	15.00 ft HDMI cable, male to male connector
Max. transfer length	Up to 50 meters for 1080p; 80 meters for 1080i		
Power supply	5VDC, 100 mA (max. working current)		
HDCP version	HDCP1.2		
Dimensions (LWH)	63 x 46 x 23mm		
Net Weight	125g (receive); 122g (transmit)		

© Copyright 2008-2012 Energy Transformation Systems, Inc FatCat5 System panels and information outlets protected under US Patent Number 6,123,577. FatCat5™, FatCat5 System™, Chameleon Color Coding System™, Balanced Star™, Balanced Line™, Monoline™ and Precision Wave™, InstaSnake™, CineSnake™ are trademarks of Energy Transformation Systems. All other brand or product names are or may be trademarks of, and are used to identify the products or services of their respective owners.

Revised 12/12/2012



Energy Transformation Systems, Inc.
43353 B Osgood Rd., Fremont, CA 94539
www.etslan.com
800-752-8208 510-656-2012 Fax 510-656-2026

