



Podblaster



Podblaster Audio Level Processing System

Digital Audio Processing at a REVOLUTIONARY price!

Solving Audio Level problems completely

Perceived loudness, dynamic range, peak level; suitable for all situations where some combination of these three must be unobtrusively controlled.

BENEFITS:

- Produces that smooth professional sound... without breaking the bank!
- Ends listener annoyance and 'tune-out' due to sloppy levels
- Allows every presenter the **freedom** to concentrate on the content
- Improves audibility and clarity of any programme
- Eliminates overload distortion and damage forever

APPLICATIONS:

- Audio level 'auto-pilot' for Podcasting
- Outside Broadcasts, news booths, unattended studios and remotes
- Cable and IP TV head-end [with optional rack-mount kit]
- STL, digital codec, PA and monitor overload protection
- Audio streaming and archiving

FEATURES:

- Powerful, yet unobtrusive level control
- Simple, easy-to-use GUI programme for setup via PC and USB
- Great audio quality. The same superb DSP module used in our professional ALPS range
- Factory presets deliver exactly the results you need for any application ...fast
- Cost-effective yet with balanced analogue I/O and S-PDIF digital I/O
- Desktop case; Half-width 1-U rack size, two can be rack-mounted side by side with optional rack mounting kit.
- Bright, Always-Visible LED bargraphs for audio confidence checks
- Low audio latency (2.2 - 4 milliseconds), fast boot-up (<1 second).
- Stereo or Dual-Mono
- 96 or 88.2kHz native mode processing avoids multiple unnecessary ASRCs



audessence.com

+44 (0) 870 850 2237

sales@audessence.com

SPECIFICATIONS

Frequency Response:

DIGITAL-DIGITAL: 20Hz-20kHz +/-0.1dB
ANALOGUE-ANALOGUE: 30Hz-20kHz +/-0.5dB

Noise:

DIGITAL-DIGITAL (rms 20Hz-20kHz): <-117dBFS
ANALOGUE-ANALOGUE: (rms 20Hz-20kHz): <-83dB ref: Limit point +8dBu

Distortion:

DIGITAL-DIGITAL (6dB limiting): <-94dB / 0.002% THD
ANALOGUE-ANALOGUE (6dB limiting): <-74dB / 0.02% THD

Stereo Separation (L/R crosstalk):

DIGITAL-DIGITAL (at 3kHz): <-117dB
ANALOGUE-ANALOGUE (at 3kHz): <-80dB

Inputs:

ANALOGUE: Balanced, 10k (bridging), 1/4" Jack [TRS].
Standard operating level -6dBu to +14dBu (+21dBu clip point)
DIGITAL: S-PDIF (RCA/Phono); 32, 44.1, 48, 88.2, 96kHz sample rate. 16, 20, or 24 bits.

Outputs:

ANALOGUE: Balanced, 1/4" jack [TRS]. Standard operating level -6dBu to +14dBu
DIGITAL: S-PDIF (RCA/Phono); full input rate / half input rate and 88.2 / 96kHz selectable.

Processing blocks:

High-pass filter: Can be set between 3Hz and 110Hz

Gated AGC: Capture range +/-20dB; maximum positive gain can be set.

Advanced AGC enables faster, programme-dependent operation. Defeatable.

Compressor: Nominal 1.5:1 slope and 4dB maximum boost of low levels. Defeatable.

Wide-band Limiter: Zero overshoot 1.3ms look-ahead zero clipping. Defeatable.

HF Limiter: Protects 50us or 75us emphasis curve for FM broadcast applications. Defeatable.

Control:

Setup is via PC only (GUI software supplied) and USB port (USB is on rear panel).

Select a factory preset, modify it for less or more processing, set levels etc, save to Flash memory.
Simplified operation of GUI does not require expert knowledge.

Every processing parameter, including all thresholds and time constants, can also be accessed and modified under PC control if desired for 'expert' setup.

Power:

5V DC / 6 Watts. External 110V or 230V AC PSU supplied.

Dimensions & weight:

44 x 217 x 228mm deep / 1.75" x 6.5" x 9" deep. Weight: 1kg / 2.2lbs

Pro Versions

For entry-level professional product (rack-mount, balanced analogue I/O, AES-3, XLRs) see our ALPS-1 product.

For full local and remote control options see our ALPS-2 and ALPS-3 products.

Warranty:

1 year return-to-base warranty

Approvals:

CE (EMC and LVD), RoHS